



BRAKE TYPE HAB-4-90 RS

HYDRAULIC APPLIED BRAKE / WITH RETRACTING SPRINGS



Description

HAB-4-90 RS is a hydraulic applied brake suitable for dynamic or static applications.

HAB-4-90 RS is a compact design with two pistons in each opposed caliper and pad release springs. Can be installed in horizontal or vertical orientation.

Main features

- Hydraulic applied brake.
- Spring released.
- Quick response and braking time.
- Reduced braking noise.
- Compact and robust design.
- Easy maintenance.
- Organic, asbestos free linings.
- Four pistons.
- Long service life.

BRAKE TYPE HAB-4-90 RS


HYDRAULIC APPLIED BRAKE / WITH RETRACTING SPRINGS

Max. Braking Force (N)	162560
Operating pressure (Mpa or N/mm ²)	16
Piston Area (mm ²)	6360
Pad area (mm ²)	19589
Max. wear of pad (mm)	7
Friction coefficient (μ)	0.4
Max working pressure (Mpa or N/mm ²)	18
Total piston area: each caliper half (mm ²)	12700
Volume for each caliper at 1 mm stroke (mm ³)	25400
Brake Disc thickness (mm)	20 - 40
Pressure connection/port	1/4" BSP
Drain connection/port	1/4" BSP
Recommended pipe size (mm)	10/8
Mounting Bolts	M24 and M27 Quality 10.9 and 12.9
Operating temperature (°C)	-30 to +60


Assembly with the Rotor Brake:

$$\text{Brake Torque} = \mu \times \text{Clamping Force} \times R' (\text{N} * \text{mm})$$

$$R' = \text{Effective radius} = R - d (\text{mm})$$



HAB-4-90 RS



Brake Torque HAB-4-90 RS (P=16Mpa)

